



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SERIES 7 RECIP

SUPER PREMIUM SYNTHETIC
COMPRESSOR FLUIDS

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SERIES 7 RECIP

AMERILUBE SERIES 7 RECIP compressor lubricants represent American Synthol's continued leadership in producing exceptional performance compressor fluids. These are blended from several synthetic base stocks, have a new advanced technology additive system, and provide outstanding performance. AMERILUBE SERIES 7 RECIP lubricants combine the best characteristics of these base stocks to form a synergistic blend of fluids and additive systems that are specially formulated for Reciprocating Compressors.

- Outstanding Oxidation Stability
 - Very High Viscosity Index
 - High Flash & Auto-Ignition Points
 - Very Low Volatility
 - Extremely High Film Strength
 - Excellent Coolant Properties
 - Very Long Life Fluid
- Energy Savings
 - Carbon and Varnish Control
 - Reduced Maintenance Costs
 - Reduced Downtime
 - Excellent Materials Compatibility
 - Reduced Lubricant Consumption
 - Excellent Rust & Corrosion Control

Typical Properties

Lubricant Designation	A 1007C	A 1557C	A 1757C	A 1807C
Viscosity Index	100	128	129	131
Viscosity cSt @ 40 °C	106	110	170	180
Viscosity cSt @ 100 °C	11.8	14.0	19.1	20.2
Viscosity SUS @ 100 °F	491.2	509.7	788	834
Viscosity SUS @ 212 °F	65.7	74.0	94.7	99.3
Flash Point °F	501	510	520	525
Auto-Ignition Point °F	800	810	825	835
Pour Point °F	-27	-27	-20	-22
Four Ball, 40 Kg, 1200 RPM, 167°F				
1 Hr, Scar Dia mm	.40	.40	.38	.38
Four Ball Weld Point, Kg	150	170	170	170
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/38/2	40/38/2	40/38/2	40/38/2