

CASTROL PowerRS TTS 2T Motor Oil

Castrol PowerRS TTS 2T Motor Oil is an advanced, synthetic 2-stroke engine oil. Its Power Protection Formula provides protection against thermal and mechanical breakdown, allowing your engine to produce maximum power without compromising protection. Suitable for pre-mix or injector use.

- Fully-synthetic 2-stroke motorcycle engine oil
 - Creates a tough, heat reactive layer of protection
 - Designed for both injection and premix lubrication up to a fuel/oil ratio of 50:1
 - Extreme protection even at maximum RPM
 - Protection against ring sticking and engine seizure
 - Protection against thermal and mechanical breakdown
 - Engine cleanliness and virtually smokeless exhaust
- For more information please visit www.castrol.com/motorcycle.

TYPICAL PROPERTIES*

Test	Method	Typical Results
API Service		TC
JASO Service		FD
ISO Service		LEGD
Specific Gravity, 60° F	ASTM D1298	0.875
Pounds per Gallon		7.3
Viscosity, cSt 100°C	ASTM D445	7.6
Flash Point, PMCC, min °C	ASTM D93	70.0
Pour Point, °C max	ASTM D97	-48
Calcium % wt.	ASTM D4951	0.039
Zinc % wt.	ASTM D4951	0.001
Phosphorus % wt.	ASTM D4951	0.001

PART NUMBER & UPC INFORMATION

Packaged Goods

	12/1 Lt Plastic	4/4 Lt Plastic
Case Size	12899	03912
Case Part No.	00361-9	00912-3
Bottle / Unit UPC	00361-9	03912-0
Case UPC		

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

© 2007 BP Lubricants USA Inc. All rights reserved.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470

Telephone: 1-800-462-0835
E-mail: contactus@bp.com
Website: www.castrol.com/atf