

V-SERIES “SS” SYNTHETIC MOTOR OIL SAE 20W/50



>>Description

Torco V-Series “SS” Synthetic Motor Oil is engineered utilizing Group IV/V synthetic base oil chemistries to provide the most shear stable and oxidation stable formula. Developed to resist extreme heat and loads encountered in V-type motorcycle engines. Torco V-Series “SS” Synthetic Motor Oil fortified with Torco’s race specific MPZ technology, which reduces frictional losses for maximum horsepower and torque output. The V-Series line is specifically formulated for Harley® and custom v-twin engines.

>>Features

- >Group IV/V 100% Synthetic Formulas
- >Maximizes horsepower & torque output by as much as 4%
- >Reduces engine temperatures
- >Highest level of engine protection.

>>Application

For use in all American-made and metric V-twin motorcycle engines. Highly recommended in extreme heat, high RPM and long operations. Exceeds manufacturer warranty requirements. Exceeds API SG / JASO-MA

>>Typical/Test Data

SAE Grade	ASTM#	20W-50
Appearance	Visual	Amber
Viscosity @ 100°C	D-445	20.98
Viscosity @ 40°C	D-445	169.26
Pour Point, °C	D-97	-39
Flash Point, °C	D-92	230

>>Directions

Follow manufacturer’s fill level requirements. Compatible with other petroleum and synthetic lubricants.

>>Package Sizes / P/N

SAE Grade	20W/50
1-Liter (1.056 US QT)	T642050CE
12/1-Liter Case	T642050C
5 Gallon Pail	T642050E
55 Gallon Drum	T642050B