



Product Description

GL-4 Hypoid Gear Oil has low pour points and high temp properties to provide lubrication over a wide temperature range. This versatile lubricant contains anti-rust and anti-wear EP additives to provide the corrosion protection in drives and hypoid gears.

Product Specifications

Applications	Auto, truck and bus standard transmissions and differentials requiring API/GL-3 and GL-4 oils
Unit Package Description	1 Quart Bottle
Brand	Sta-Lube
Generic Description 1	Multi Purpose Gear Oil SAE 140W
Net Fill	32 Fl Oz
UPC Code	0 72213 24228 7
Unit Dimensions-Inches	7.5H x 2.25W x 4.75D
Units Per Case	12
Case Dimensions-Inches	9H x 10W x 16.25D
Cases Per Pallet	91
Lbs. Per Case	28
I 2 of 5 Code	30072213242288
Appearance	Amber Liquid
Odor	Mild
Flashpoint - TCC Method	>302°F
Specific Gravity	0.89 to 0.91
Flammability	Non-flammable
Plastic Safe	Yes
SAE Grade	140
ISO Viscosity Grade	460
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	None
VOC g/L (Federal)	None
VOC Lbs./Gal. (Federal)	None
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.