



**Product Description**

GL-5 Heavy Duty Gear Oil is an extreme pressure, multi-purpose, automotive gear lubricant. Excellent performance for differentials operating under high speed, low torque; and low speed, high torque conditions. It meets SAE, military and commercial specs.

**Product Specifications**

<b>Applications</b>	For complete fill or topping off of: manual transmissions, hypoid type differentials, limited-slip/twin grip/trac-lok/sure-grip differentials. Performance equivalent to Ford M2C197A, Chrysler MS9020, Mack GO-H, G, & F.
<b>Unit Package Description</b>	1 Gallon Bottle
<b>Brand</b>	Sta-Lube
<b>Generic Description 1</b>	Limited Slip Gear Oil SAE 75W90
<b>Net Fill</b>	1 Gal
<b>UPC Code</b>	0 72213 24630 8
<b>Unit Dimensions-Inches</b>	10.63H x 4.75W x 6D
<b>Units Per Case</b>	4
<b>Case Dimensions-Inches</b>	11.25H x 11.25W x 13.5D
<b>Cases Per Pallet</b>	55
<b>Lbs. Per Case</b>	33
<b>I 2 of 5 Code</b>	30072213246309
<b>Appearance</b>	Dark Amber Liquid
<b>Odor</b>	Mild Petroleum
<b>Flashpoint - TCC Method</b>	>302°F
<b>Specific Gravity</b>	0.87 to 0.91
<b>Flammability</b>	Non-flammable
<b>Plastic Safe</b>	Yes
<b>SAE Grade</b>	75W90
<b>ISO Viscosity Grade</b>	None
<b>DOT Proper Shipping Name</b>	Not Regulated
<b>VOC % (Federal)</b>	None
<b>VOC g/L (Federal)</b>	None
<b>VOC Lbs./Gal. (Federal)</b>	None
<b>VOC Category</b>	Not Regulated
<b>Removal (How To)</b>	Remove with a degreaser or brake cleaner product.