



Product Description

GL-5 Heavy Duty Gear Oil is an extreme pressure, multi-purpose, automotive gear lubricant. Excellent performance for differentials operating under high speed, low torque; and low speed, high torque conditions. It meets SAE, military and commercial specs.

Product Specifications

Applications	For complete fill or topping off of: manual transmissions, hypoid type differentials, limited-slip/twin grip/trac-lok/sure-grip differentials. Performance equivalent to Ford M2C197A, Chrysler MS9020, Mack GO-H, G, & F.
Unit Package Description	1 Quart Bottle
Brand	Sta-Lube
Generic Description 1	Limited Slip Gear Oil SAE 80W90
Net Fill	32 Fl Oz
UPC Code	0 72213 24720 6
Unit Dimensions-Inches	7.5H x 2.5W x 4.75D
Units Per Case	12
Case Dimensions-Inches	9H x 10W x 16.25D
Cases Per Pallet	91
Lbs. Per Case	27
I 2 of 5 Code	30072213247207
Appearance	Dark Amber Liquid
Odor	Mild Petroleum
Flashpoint - TCC Method	>302°F
Specific Gravity	0.87 to 0.91
Flammability	Non-flammable
Plastic Safe	Yes
SAE Grade	80W90
ISO Viscosity Grade	150
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	None
VOC g/L (Federal)	None
VOC Lbs./Gal. (Federal)	None
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.