

CASTROL Hypoy C Gear Oil

Castrol Hypoy C Gear Oil is a multi-grade gear lubricant that provides excellent performance in manual transmissions and heavy-duty truck systems.

Available Grades

- **Hypoy C 75W-90:** exceeds API Service GL-5 lubricant for extreme pressure conditions and provides superior low temperature performance for smoother gear shifting and differential operation in colder climates. Maintains a thick oil film even under higher temperatures and is recommended for service fill of limited slip differentials calling for an API Service GL-5, SAE 75W-90 gear oil.
- **Hypoy C 80W-90:** exceeds API MT-1 lubricants for non-synchronized manual transmissions used in buses and heavy duty trucks as well as API Service GL-5 lubricant for extreme pressure conditions. Recommended for service fill of all limited slip differentials in passenger cars and light trucks calling for SAE 80W-90 and API Service GL-5 specifications. Recommended for applications calling for Ford ESP-M2C154-A and GM 9985290 and is Mack GO-H approved.
- **Hypoy C 85W-140:** exceeds API MT-1 lubricant for non-synchronized manual transmissions used in buses and heavy-duty trucks as well as API Service GL-5 lubricant for extreme pressure conditions.
- For more information please refer to your owner's manual or visit www.castrol.com.

TYPICAL PROPERTIES*

Test	Method	-----Typical Results-----		
		75W-90	80W-90	85W-140
Grade		75W-90	80W-90	85W-140
API Service		GL-5	GL-5, MT-1	GL-5, MT-1
Viscosity, cSt 100°C	ASTM D-445	17.5	14.1	28.0
Low Temp.(°C) Brookfield Vis. cst., max	ASTM D-2983	135,000 (-40)	130,000 (-26)	130,000 (-12)
Pour Point, °C max	ASTM D-97	-39	-30	-12
Flash Point, COC, °F(°C) min	ASTM D-92	390 (198)	390 (198)	390 (198)
Specific Gravity, 60°F	ASTM D-1298	0.896	0.890	0.896
Pounds per Gallon		7.46	7.41	7.46

PART NUMBER & UPC INFORMATION

Grade	75W-90		80W-90		85W-140
Packaged Goods					
Case Size	12/1 Qt		12/1 Qt		12/1 Qt
Case Part No.	12651		12609		12621
Bottle / Unit UPC	0-79191-00651-1		0-79191-00609-2		0-79191-00621-4
Case UPC	0-79191-12651-6		0-79191-12609-7		0-79191-12621-9
Pail / Drum / Bulk					
Unit Size	120 lb Drum	400 lb Drum	35 lb Pail	120 lb Drum	400 lb Drum
Part No.	0651	0653	0612	0611	0614
	120 lb Drum 0621				

Note: This information is based on products sold in the U.S. Due to continual product research and development, the information is subject to change without notification. Typical properties may vary slightly.

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

© 2007 BP Lubricants USA Inc. All rights reserved.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470

Telephone: 1-800-462-0835
E-mail: contactus@bp.com
Website: www.castrol.com

IT'S MORE THAN JUST OIL. IT'S LIQUID ENGINEERING.™

