



Product Data

Castrol Optigear BM

Gear oils with MFT

Description

Castrol Optigear™ BM are solid-free high performance gear oils containing the additive combination Microflux Trans™ (MFT). Designed to reduce wear caused by surface fatigue, pitting, spalling, scuffing, scoring or irregularities during running-in period and during normal operations.

Microflux Trans (TRANS=TRiple Action Non-sacrificial Surface engineering) improves friction surfaces to an extent not possible with normal machining processes and conventional Extreme Pressure (EP) lubricants. In a tribological system, the polarized MFT additives instantaneously create a passive film on friction surfaces before friction occurs. At a given load level, the MFT additives create a resistant protective layer on friction surfaces. Under severe load, components of the MFT additive combination are activated and diffuse into the surfaces initiating an improvement of their friction characteristics through plastic deformation. The organic reaction products become a component of the tribopolymer system. Unlike the case with conventional lubricants, the tribopolymers formed by MFT are long-chained compounds with excellent lubricity and adhesion. The load carrying area is improved and the hydrodynamic lubrication film is easier to maintain. This unique physical-chemical reaction is Castrol surface engineering and achieves a non-sacrificial micro-smoothing of the friction surfaces. The MFT additive technology provides optimum wear protection and an extremely low coefficient of friction even under extremes of pressure, vibration, shock loads, at high or low speeds or varying operational conditions.

Optigear BM gear oils are in conformity with and even exceed the requirements of DIN 51517 part 3 CLP and AGMA specifications 9005-D94 for EP Gear Oil.

Application

In all types of industrial gears, especially operating under extremely heavy loads, where conventional EP oils fail.

- Long term lubrication under the most extreme mechanical conditions, vibrations and elevated temperatures.
- Spur and bevel gears, worm gears up to the medium load range
- Gears exposed to high sliding friction and high Hertzian surface pressures up to 2000 N/mm² (elevators, rolling mills, belt conveyors, extruders, vibrating equipment, crushers, high speed looms and separators).
- Eccentrics, cam shafts and planetary gears.
- Variable speed drives (PIV).
- Sealed gear couplings.
- In all types of bearings, especially for spherical roller bearings, full complement cylindrical roller bearings and thrust bearings.
- Circulation systems.

Advantages

- Extended life time of machine elements and wear parts, lower maintenance and labour costs by minimised wear and friction.
- Full load operation within shortest time, virtually eliminating the running-in period.
- Lower costs for lubricants and waste oil disposal because of significant extensions of both service life and re-lubrication intervals.
- Energy savings due to reduced coefficient of friction, lower temperature of lubricant and component and improvement in operating efficiency.
- Product consolidation, i.e. simplification and reduction of lubricants and spare parts.
- Reduction of noise resulting from high frequency stick-slip for "life" lubrication in some applications.
- Smoothing of existing pittings.

Typical Characteristics

Test	Method	Units	BM 100	BM 150	BM 220	BM 320	BM 460	BM 680	BM 1000	BM 3000	
Colour	Visual	-	brown	brown	brown	brown	brown	brown	brown	brown	
ISO viscosity group	ASTM D 2422	-	100	150	220	320	460	680	1000	3000	
AGMA Lubricant Number	-	-	3EP	4EP	5EP	6EP	7EP	8EP	8AEP	-	
Specific gravity @ 60°F	ASTM D 1298	g/cm ³	0.89	0.89	0.90	0.91	0.91	0.92	0.92	0.91	
Kin.viscosity, @ 40°C / 104°F	ASTM D 445	mm ² /s	101	157	218	320	459	670	1000	3000	
Kin.viscosity, @ 100°C / 212°F	ASTM D 445	mm ² /s	11.4	15.0	18.8	24.3	30.6	37.8	50.0	122	
Viscosity index	ASTM D 2270	VI	100	100	95	95	95	95	95	120	
Flash Point, COC	ISO 2592 / ASTM D92	°C	230	230	235	240	240	250	260	260	
		°F	446	446	455	464	464	482	500	500	
Pour Point	ISO 3016 / ASTM D97	°C	- 21	- 18	- 15	- 15	- 12	- 9	- 9	0	
		°F	- 5.8	- 0.4	5.0	5.0	10.4	15.8	15.8	32.0	
Copper Corrosion (3 hrs @ 100°C)	ISO 2160 / ASTM D130	-	1a	1a	1a	1a	1a	1a	1a	1a	
Rust Test	ISO 7210 / ASTM D665										
Procedure A (24 hrs Distilled Water)			Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	
Procedure B (24 hrs Synthetic Sea Water)			Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	
SRV-Test mode 5 ae: Wear scar diameter	DIN E 51834	mm	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	
Min. friction coefficient μ		-	0.060	0.060	0.060	0.060	0.060	0.060	0.060	0.060	
Max.friction coefficient μ		-	0.080	0.080	0.080	0.080	0.080	0.080	0.080	0.080	
FZG Test, (A/8.3/90)	DIN 51354		>12								
FZG micropitting test	FVA No. 54		10								
Foam Sequence I	ISO 6247 / ASTM D892	mls	0/0								-

Subject to usual manufacturing tolerances.

Please note values in blue are USA values for Specific Gravity and Viscosity. For USA these replace European values shown in black

Additional Information

- Miscible and compatible with unleaded gear oils based on mineral oil. However, maximum performance is only guaranteed if not mixed with any other product.
- Compatible with non-ferrous metals.
- Compatible with paints and conventional sealing materials.
- Mechanical cleaning with all known filtering installations and separators possible.

Castrol Optigear BM
4/14/2006, Global Version Number 1
Castrol, Optigear and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial