

Product Information

Specialty Lubricants

DOW CORNING

Molykote® G-1502FG

Synthetic Chain & Open Gear Grease

FEATURES

- White color
- Fully synthetic base oil
- Meets FDA regulation 21 CFR 178.3570 for incidental food contact applications
- NSF H1 approved
- Wide service temperature range

BENEFITS

- Resists water wash off and spray off
- Excellent shear stability
- Formulated to provide higher oxidation resistance, corrosion protection, load carrying capability and longer service life than conventional lubricants
- Provides good compatibility with most industrial and engineering substrates including many plastic and rubber materials

COMPOSITION

- Aluminum complex thickener
- ISO 220 100% Polyalphaolephin (PAO) base oil
- Fortified with carefully formulated synergistic combination of lubricating solids

NLGI #2.5 white grease, meets FDA regulation 21 CFR 178.3570 as a lubricant with incidental food contact

APPLICATIONS

- Suitable for applications where tacky grease is preferred or required such as chains, cams, open gears, valves and sprockets where water wash off is problematic or grease sling-off can not be tolerated

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

CTM*	ASTM*	Property	Unit	Value
	D 445	Base Oil Viscosity at 104°F (40°C)	cSt	220
	D 445	Base Oil Viscosity at 212°F (100°C)	cSt	25.2
	D 2270	Viscosity Index		145
	D 217	Penetration, Unworked, 77°F (25°C), mm/10	mm	255
	D 217	Penetration, Worked, 77°F (25°C), mm/10 (W/60)	mm	250
	D 2265	Dropping Point, °F (°C), min		520
	D 2266	Four Ball Wear, 40kg, 1200 rpm, 75°C, max	mm	0.60
	D 2596	Four Ball EP, Weld Load, min	Kg	500
	D 2509	Timken OK Load, min Temperature Range, estimated, °F (°C)	lb (KG)	50 (110) -40 to 300 (-40 to 149)
	D 1743	Rust Test		PASS
	D 4048	Copper Corrosion		1B

*CTM: Corporate Test Method, copies of CTM's are available on request.

HOW TO USE

Apply using conventional grease application methods, i.e., clean brush, and manual or automated dispensing equipment.

HANDLING PRECAUTIONS

Product safety information required for safe use is not included. Before handling, read product and safety data sheets and container labels for safe use, physical and health hazard information. The material safety data sheet is available on the Dow Corning website at www.dowcorning.com. You can also obtain a copy from your local Dow Corning sales representative or Distributor or by calling your local Dow Corning Global Connection.

USABLE LIFE AND STORAGE

When stored at or below 40°C (104°F) in the original unopened containers, this product has a usable life of 60 months from the date of production.

PACKAGING

This product is available in cartridges, pails and drums.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support Customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our website, www.dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

We help you invent the future.™

www.dowcorning.com