



GENERAL MAINTENANCE LUBRICANT



LUBRICANTS



SPRAYON® HEAVY DUTY OPEN GEAR & WIRE ROPE LUBE

- Prevents rust & corrosion
- Withstands extreme pressure
- Works from 0°F to 450°F
- Will not become brittle or breakdown while working



CLEANERS, DEGREASERS
LUBES AND SEALANTS

SUPERIOR
LUBRICANTS

PAINTS, COATINGS
AND PRIMERS

CAULKS, SEALANTS
AND ADHESIVES

BRUSHES, ROLLER COVERS
AND ACCESSORIES

Sprayon® Heavy Duty Open Gear & Wire Rope Lube is a high performance lube that penetrates the pores of metal surfaces to reach the core of wire rope. This heavy duty lubricant provides a wide range of lubrication at high temperatures while adhering extremely well to surfaces. It “travels” on metal surfaces to actually displace water, resulting in excellent rust protection. Equipped with an extension tube for hard-to-reach areas or for use while equipment is in operation.



PROPERTIES

APPEARANCE: Viscous black film

ODOR: Mild solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 6.16

SPECIFIC GRAVITY: 0.74

PAINTABLE: No

H.A.P.S. (Hazardous Air Pollutants): No

SARA 313 Chemicals: No

% VOC AEROSOL: 60.00%

% VOC BULK: 42.90%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING:

S00201 - 2,4,0;

201LQ - 2,3,0

SHELF LIFE: 3 years from date of manufacturer.

PERFORMANCE

PLASTIC SAFE: No

TEMPERATURE RANGE:

LOW: 0°F

HIGH: 450°F

LOAD CAPACITY: Extreme pressure

- NSF Registration Number 131586; H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- Quiets, lubricates and protects
- Will not wash or weather away
- Displaces moisture

Distributed By:

- Black color assists in showing complete coverage
- Ideal for indoor or outdoor use
- Equipped with an extension tube for hard-to-reach areas

USES

- Open or exposed gears
- Gear boxes
- Wire rope
- Winches
- Cable
- Metal forming presses
- Roller chains
- Machine tools
- Wire rope (in use or in storage)

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale.

Aerosol Application: Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 14" from surface.

PACKAGING

Stock #: S00201

UPC Code: 0-75577-90201-9

Fill Wt.: 12 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

Stock #: 201LQ

UPC Code: 0-75577-20199-0

Fill Wt.: 14 fl. oz.

Per Case: 12

Carton Dimensions:

L 11.12" x W 8.43" x H 10.18"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: www.KPG-Industrial.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486



Nonfood Compounds
Program Listed (H2 Rated)
(Registration #131586)



INDUSTRIAL

Krylon Products Group

101 Prospect Ave. NW
Cleveland, OH 44115
www.KPG-Industrial.com
Tel: 1-800-777-2966