

PRODUCT INFORMATION SHEET

ZENEX

P.O. Box 461016 • Cleveland, Ohio 44146
Toll Free: 866-217-5100 • Fax: 440-786-7233

ZenaLube Gear

Open Gear Lubricant

ZENEX NUMBER 495505

DESCRIPTION

A lubricant with excellent adhesion and heavy viscosity providing a tough lubrication that will not drop or be thrown off.

FEATURES AND BENEFITS

The tacky adhesiveness of this product continuously recoats and lubricates all gear surfaces. Extremely effective when used underwater. Forms a film that resists rust and corrosion. Increases life of all gears. Extreme pressure capacity minimizes squeeze-out.

APPLICATIONS AND USES

For open or exposed chains, wire, rope or cables on heavy loads and extreme pressure, snow removal equipment, marine and dockside equipment, elevators, cranes, and drag lines.

DIRECTIONS FOR USE

Shake can well before using. Spray liberally in short bursts from 12 to 15 inches. Repeat as needed.

SIZE / AVAILABILITY

20-oz. Aerosol
Net Weight 14 oz.
12 per case



**Emergency
Phone Number
(800) 535-5053**

HMIS	
HEALTH	2
FLAMMABILITY	4
REACTIVITY	0
PERSONAL PROTECTION	B

