



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE LITHIUM BRICK GREASE

LUBRIPLATE Lithium Brick Grease is recommended to meet the lubrication requirements of open slot or open well type bearings where the brick grease rides directly on the bearing shaft. The rotating motion of the bearing shaft wipes a film of lubricant onto the bearing surfaces keeping it properly lubricated.

LUBRIPLATE Lithium Brick Grease comes in 4-lb. Bricks (12 Bricks per Case). These Bricks are easily cut into smaller pieces to place in the bearing opening. The size of the piece should be small enough to allow freedom of movement of the block while riding on the bearing surface. From time to time, it is also a good practice to turn or rotate these pieces. Also, do not over load or over pack the bearing opening or slot.

Applications for LUBRIPLATE Lithium Brick Grease are commonly found at rock quarries and paper mills.

Typical Tests

| | |
|-----------------------------------|--------------------|
| N. L. G. I. | 7 |
| Unworked Penetration @ 77°F | 45 - 65 |
| Dropping Point | 325°F/165°C |
| Mineral Oil Base Viscosity | |
| SUS @ 100°F | 450 - 550 |
| cSt @ 40°C | 100 |
| Viscosity Index | 80 |
| Soap | Lithium 12-Hydroxy |
| % of Thickener | 12 - 18 |
| Color | Amber |
| Texture | Smooth |
| <u>Packaging Available</u> | <u>Part No.</u> |
| 48 lb. Carton (12 - 4-lb. Bricks) | L0132-038 |