



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE "SFL" SERIES

Synthetic, Food Grade Lubricating Greases

*NSF H-1 Registered

"These products are certified OU Kosher Pareve"

"These products are Halal certified"

The LUBRIPLATE SFL Series was developed to meet the ever-increasing demands placed on food-processing equipment today. The synthetic base fluid and the aluminum complex soap thickener allows for a wide operating temperature range for all four NLGI consistencies.

LUBRIPLATE SFL-1 has an approximate operating temperature range of -60 to 300°F making it ideal for freezer and other cold temperature applications where conventional food-grade greases cannot be used. In addition to its exceptional low temperature pumpability, its high shear stability, excellent water resistance and outstanding load-carrying properties make LUBRIPLATE SFL-1 the only choice for extreme low temperature applications requiring a product that meets USDA 1998 Guidelines and is NSF H-1 Registered. Available in 14½ oz. Cartridges.

LUBRIPLATE SFL-0 and LUBRIPLATE SFL-00 are similar to SFL-1 with the exception that they have softer consistencies, which are NLGI 0 and NLGI 00 respectively. LUBRIPLATE SFL-0 and LUBRIPLATE SFL-00 also have an approximate operating temperature range of -60 to 300°F.

LUBRIPLATE SFL-2 is a synthetic multi-purpose food-grade grease, which can be used throughout most modern food processing plants for most all grease lubrication requirements. This product has an approximate operating temperature range of -25 to 400°F.

Typical Tests

	<u>SFL-2</u>	<u>SFL-1</u>	<u>SFL-0</u>	<u>SFL-00</u>
Thickener	Aluminum Complex	Aluminum Complex	Aluminum Complex	Aluminum Complex
NLGI Grade	2	1	0	00
Penetration Range - 60 Strokes	265 - 295	310 - 340	355 - 385	400 - 430
Dropping Point	500°F/260°C	450°F/232°C	425°F/218°C	400°F/204°C
Low Temperature Torque @ -40°F				
Starting Torque	-----	1,853 gm-cm	618 gm-cm	358 gm-cm
Running Torque - One Hour	-----	260 gm-cm	137 gm-cm	163 gm-cm
Water Washout @ 175°F	2.5%	6.3%	8.1%	12.5%
Four-Ball Wear Test				
40 kg, 1200 rpm, @ 167°F				
Scar Diameter	0.60 mm	0.59 mm	0.55 mm	0.55 mm

(Over)

LUBRIPLATE “SFL” Series:**Typical Tests** (Cont'd.)

	<u>SFL-2</u>	<u>SFL-1</u>	<u>SFL-0</u>	<u>SFL-00</u>
Lincoln Ventmeter Results				
75°F (24°C)	N/A	200 psig	0 psig	0 psig
30°F (-1°C)	N/A	325 psig	0 psig	0 psig
0°F (-18°C)	N/A	500 psig	150 psig	150 psig
-30°F (-34°C)	N/A	1050 psig	800 psig	650 psig

Base Fluid Properties

Saybolt Viscosity @ 100°F	1070 SUS	200 SUS	200 SUS	200 SUS
Saybolt Viscosity @ 210°F	105 SUS	49 SUS	49 SUS	49 SUS
Kinematic Viscosity @ 40°C	219 cSt	39 cSt	39 cSt	39 cSt
Kinematic Viscosity @ 100°C	21 cSt	7 cSt	7 cSt	7 cSt
Viscosity Index	114	127	127	127
Flash Point	400°F/204°C	400°F/204°C	400°F/204°C	400°F/204°C
Pour Point	-25°F/-31°C	-60°F/-51°C	-60°F/-51°C	-60°F/-51°C

Statement of Usage:

“These compounds may be used on food, beverage and pharmaceutical processing and packaging equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures and as a lubricant for machine parts and equipment in locations in which there is potential exposure of the lubricated part to food, beverage, pharmaceutical and related packaging equipment. The amount used should be the minimum required to accomplish the desired technical effect on the equipment.”

Packaging Available

	<u>SFL-2</u>	<u>SFL-1</u>	<u>SFL-0</u>	<u>SFL-00</u>
35 lb. Pail	L0198-035	L0197-035	L0196-035	L0195-035
120 lb. Drum	L0198-039	L0197-039	L0196-039	L0195-039
420 lb. Drum	L0198-040	L0197-040	-----	-----
Case, 40/14½ oz. Cartridges	L0198-098	L0197-098	-----	-----

	<u>SFL-2</u>	<u>SFL-1</u>	<u>SFL-0</u>	<u>SFL-00</u>
*NSF H-1 Registration No's (Meets USDA 1998 Guidelines)	113093	043677	119618	113092

*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.