

### **CAM2 ALL SEASON ANTI-WEAR HYDRAULIC OIL**

CAM2 ALL SEASON ANTI-WEAR HYDRAULIC OIL is a very high viscosity index hydraulic oil for use in mobile and industrial equipment operated in a wide range of sub-arctic and temperate climates. This product meets API viscosity 5W-20. ALL SEASON=S formulation offers superior shear stability performance.

CAM2 ALL SEASON AW HYDRAULIC OIL is a premium anti-wear hydraulic fluid with outstanding low temperature characteristics. It is specially formulated for use in mobile equipment hydraulic circuits where wide temperature ranges are encountered. (Cherry pickers, bucket trucks and marine hydraulics).

It also can be used for traditional in-plant hydraulic applications, and exceeds most industry hydraulic fluid specifications, including:

Denison HF-2, HF-0  
Vickers  
Cincinnati Milacron  
Jeffrey

Commercial Shearing  
Sunstrand  
Rexnord  
Racine

#### **TYPICAL PROPERTIES:**

#### **ALL SEASON HYDRAULIC OIL**

SAE Viscosity	5W-20
ISO Viscosity	32
Viscosity @ 100EF, SUS	125-160
Viscosity @ 210EF, SUS	44
Viscosity Index	150
Pour Point, E F	-40
Flash Point, EF	390
Oxidation Test Hours to 2.0 acid number	2500+
Low Temperature Pumpability	Pass
Dielectric, min. KV	+35
Rust Test	Pass

7/1/2007