



Automatic Transmission Fluid

PRODUCT SPECIFICATION SHEET

FS Automatic Transmission Fluid is approved for use in all automatic transmissions that specify either a General Motors DEXRON® -III or a Ford MERCON® fluid. FS ATF has excellent oxidation stability, low temperature properties and helps minimize the formation of sludge and varnish.

FS ATF meets the requirements for the new GM DEXRON® -III H Revision specification, and may be used in previous applications requiring a DEXRON® fluid. FS ATF also meets the requirements for Allison C-4, Caterpillar TO-2 and Sunstrand Hydrostatic transmissions. FS ATF can also be used for mobile hydraulic and some industrial applications that operate over a varying temperature range.

RECOMMENDED FOR USE IN:

General Motors Automatic Transmissions
Ford Automatic Transmissions
Chrysler, AMC/Jeep/Eagle Automatic Transmissions
Some hydraulic systems and hydrostatic drives

(Always check owner's manual for proper recommendation.)

MEETS performance requirements of:

GM DEXRON® -III H, DEXRON-II, ®6137M'90,
Ford MERCON®
Ford M2C138-CJ
Ford M2C166-H
Chrysler MS-7176 (top off only)
AMC/Jeep/Eagle
Allison C-3, C-4
(DEXRON® is a registered trademark of GM Corporation)
(MERCON® is a registered trademark of Ford Motor Company)
Hydraulic Systems:

Hagglunds-Denison HF-0, HF-1, HF-2
Sperry Vickers I-286-S, M-2950-S, 35VQ25
Sunstrand Hydraulics
Cincinnati Milacron



SPECIFICATIONS:

API Gravity @ 60° F	31.0
Flash Point ° F	320
Viscosity @ 100° C	7.10
Viscosity @ 40° C	33.4
Viscosity Index	163
Pour Point ° F	-48
Color (D-1500)	Red
Foaming Characteristics:	0/0/0

(Subject to change without notice.)
Revised 08/03/2005